

ClayTec Glass mash 112 fire protect

Item No. 35.018

- **For planking and lining systems made of clay building boards with fire protection requirements**



Surface reinforcement for Clay adhesive and reinforcing mortar and all clay plasters. ClayTec Glass mesh 112 fire protect is a gauze made from glass silk yarn/roving, finished with special fire-protection treatment. It has high tensile strength, is very fine, and is particularly easy to work with. Due to its building material class A2, non-combustible, this mesh is suitable for all drywall wall constructions with fire protection requirements.



GERMANY
© ClayTec GmbH & Co. KG
Nettetalter Straße 113-117
D-41751 Viersen-Boisheim
+49 (0)2153 918-0
service@claytec.com
claytec.com

2026/9
Changes and errors excepted.
Current version available at
claytec.com

ClayTec Glass mash 112 fire protect

Item No. 35.018

Application Used as surface reinforcement for planking and lining systems made of clay building boards, for example ClayTec Clayboard heavy, item No. 09.014 and 09.015.

Properties Gauze made from glass silk yarn/roving, finished with a special fire-protection treatment. Weight approx. 112 g/m², warp/weft approx. 16/15 threads per 10 cm, mesh size approx. 5.0 x 5.5 mm. Alkali-resistant. Building material class A2, non-combustible..

Delivery Form On rolls. For surface reinforcement: width 100 cm, length 100 m, ClayTec 35.018.

Storage Can be stored for at least three years if kept dry, well-ventilated, and protected against direct sunlight.

Material Requirement Surface reinforcement: equal to m² plaster surface plus an additional 10-20 % extra for waste and overlapping.

Application Method The mesh is laid on the mortar while it is still freshly applied and plastic, and rubbed in with a sponge board or similar. Approx. 10 cm overlap must be provided in areas around joints.

Claims for compensation that do not result from factory mixing errors are excluded. Subject to change and errors excepted. As of 2026/9.